



EDGE® GRAPPLES

Similar in application to the compact loader grapples, the excavator grapple is designed to handle objects varying in size and shape. Remove large rocks, brush and debris with the excavator grapple. These grapples are not designed for digging or prying.

OPERATIONAL BASICS

This attachment requires that a set of ears be welded to the excavator, then the operator can use the bucket curl cylinder to close the grapple. No auxiliary hydraulics are required for operation. Available in sizes from 24" (610 mm) to 36" (914 mm).

Demolition and forestry type applications require additional operator protection, such as a poly-carbonate front window. Check application requirements.

SPECIFICATIONS

Width (in/mm)	Weight (lbs/kg)
24/610	650/295
30/762	900/408
36/914	1050/476

FEATURES

- All sizes feature a 42" (1067 mm) opening
- Available in sizes from 24" (610 mm) to 36" (914 mm)
- Three tines on the top and two tines on the bottom

	Gehl Compact Excavators						Mustang Compact Excavators					
	Z17	Z25	Z35	Z45	Z55	Z80	170Z	250Z	350Z	450Z	550Z	800Z
Machine Compatibility												
*Excavator Grapples		◆	◆	◆	◆	◆		◆	◆	◆	◆	◆

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment