



### EDGE® THUMBS

EDGE hydraulic thumbs are specifically designed to aid in handling or loading irregular shaped objects or debris. The thumbs are not intended to be used for prying or ripping.

### OPERATIONAL BASICS

EDGE hydraulic thumbs easily retract back against the dipper, so it can be left on the machine during normal excavation. They use high strength steel throughout the weldment and hardened bushings are used at all pivot points.

The hydraulic thumbs feature a single cylinder and dual tines constructed of high strength steel with serrated edges for added durability and secure clamping. Custom designed for perfect fit up to bucket and compact excavator setup. Must specify bucket, machine model, and quick coupler used when ordering. The necessary hoses, hydraulic couplers, and relief valves are available and sold separately.

### FEATURES

- Available in either hydraulic or rigid mount
- The thumbs retract back against the dipper, so it can be left on the machine during normal excavation
- High strength steel is used throughout the weldment and hardened bushings are used at all pivot points
- Hydraulic thumbs feature a single cyline and dual tines with serrated edges
- Must specify bucket, machine model, and quick coupler when ordering hydraulic thumb



Machine Compatibility	Gehl Compact Excavators						Mustang Compact Excavators					
	Z17	Z25	Z35	Z45	Z55	Z80	170Z	250Z	350Z	450Z	550Z	800Z
*Thumbs	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆

\*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment