



EDGE® ANGLE BROOM

The EDGE angle broom cleans up just about anything, anywhere. This compact loader attachment can be used year-round and is an excellent tool to assist in the removal of snow or debris on sidewalks, parking lots and more.

OPERATIONAL BASICS

The EDGE angle broom features 50/50 poly/wire combo brush material. Angle brooms also feature a fold-away stand to protect the bristles during storage. They are available in widths ranging from 48" (1219 mm) to 96" (2438 mm), and have a manual angle up to 30 degrees. Angle brooms come complete with a hose saver kit, hoses and flat face couplers. Optional items include a hydraulic angle kit as well as an optional dust control kit which helps to reduce dust and flying debris.



SPECIFICATION

| Model | Weight (lbs/kg) | Hyd. Req. (gpm/lpm) | Angled Path (in/mm) | Brush Dia. (in/mm) | No. of Brush Segments | No. of Motors | Brush Type |
|---------|-----------------|---------------------|---------------------|--------------------|-----------------------|---------------|------------|
| AB48-26 | 380/172 | 8-15/30-57 | 41.5/1054 | 26/660 | 25 | 1 | Poly/Wire |
| AB60-26 | 440/200 | 8-15/30-57 | 52/1321 | 26/660 | 32 | 1 | Poly/Wire |
| AB60 | 793/360 | 12-25/45-95 | 54/1372 | 32/813 | 29 | 1 | Poly/Wire |
| AB72 | 852/387 | 12-25/45-95 | 64/1626 | 32/813 | 35 | 1 | Poly/Wire |
| AB84 | 915/415 | 12-25/45-95 | 75/1905 | 32/813 | 41 | 1 | Poly/Wire |
| AB96 | 953/432 | 12-25/45-95 | 85/2159 | 32/813 | 47 | 1 | Poly/Wire |
| AB72D | 890/404 | 18-36/68-136 | 64/1626 | 32/813 | 35 | 2 | Poly/Wire |
| AB84D | 953/432 | 18-36/68-136 | 75/1905 | 32/813 | 41 | 2 | Poly/Wire |
| AB96D | 793/360 | 18-36/68-136 | 85/2159 | 32/813 | 47 | 2 | Poly/Wire |

FEATURES

- 26" (660 mm) and 32" (813 mm) diameter poly/wire brushes for long life
- Use year-round for removal of snow, leaves, wood chips and more
- Optional dust control kit reduces dust and flying debris

| Machine Compatibility Gehl / Mustang | Radial Skid Loaders | | | | | | | Vertical Skid Loaders | | | Track Loaders | | | Articulated Loaders | | | |
|---|---------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------|---------------|----------------|------------------|------------------|------------------|---------------------|-----|-------------|-------------|
| | 3640E/ 2026 | R135/ 1350R | R150/ 1500R | R165/ 1650R | R190/ 1900R | R220/ 2200R | R260/ 2600R | V270/ 2700V | V330 3300V | V400/ 4000V | RT175/ 1750RT | RT210/ 2100RT | RT250/ 2500RT | 340 | 540 | 650/ 608 | 750/ 708 |
| *Angle Broom | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ |

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment