



TREE TRANSPLANTER



EDGE® TREE TRANSPLANTER

Landscape professionals and nurserymen can transform their compact equipment into useful and profitable tools for tree and shrubbery planting, transplanting and removal with the EDGE tree transplanter.

OPERATIONAL BASICS

Take advantage of the power of your compact loader with the EDGE tree transplanter. Transplant mature trees with up to 50" (1270 mm) root balls. This unit comes standard with 3, 4, or 6 semi-truncated 1/4" high alloy steel blades and additional valve port for operating rear stabilizers. Each unit comes complete with hoses and flat face couplers.



SPECIFICATION

Model	Description	Weight (lbs/kg)	Ball Dia. (in/mm)	No. of Blades	Hyd. Req. (gpm/lpm)	Overall Width (in/mm)	Length (in/mm)
TTS324	24" Tree Transplanter-Standard Duty	990/449	24/610	3	5-25/19-94	75/1905	68/1727
TTS330	30" Tree Transplanter-Standard Duty	1450/658	30/762	3	5-25/19-94	90/2286	81/2057
TTS440	40" Tree Transplanter-Standard Duty	1850/839	40/1016	4	5-25/19-94	84/2134	84/2134
TTS650	50" Tree Transplanter-Standard Duty	3025/1372	50/1270	6	5-25/19-94	96/2438	112/2845

FEATURES

- Transplant mature trees with up to 50" (1270 mm) root balls
- Comes standard with 3, 4, or 6 semi-truncated 1/4" high alloy steel blades
- Each unit comes complete with hoses and flat face couplers

	Radial Skid Loaders							Vertical Skid Loaders			Track Loaders			Articulated Loaders			
	3640E/2026	R135/1350R	R150/1500R	R165/1650R	R190/1900R	R220/2200R	R260/2600R	V270/2700V	V330/3300V	V400/4000V	RT175/1750RT	RT210/2100RT	RT250/2500RT	340	540	650/608	750/708
Machine Compatibility Gehl / Mustang																	
*Tree Transplanter		◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment