GEHL®

650 & 750 ARTICULATED LOADERS



KEY FEATURES



4-Post Canopy ROPS and FOPS Certified



Cabin with Heat and Air Conditioning*



Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump



Hydrostatic Transmission with Inching Pedal



Digital Display with Audible and Visual Indicators



Differential Lock (Hydraulically Activated Front and Rear)



Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)



Tapered Z-Bar Loader Linkage with Mechanical Self-Level and Return-to-Dig



Tilt and Lift Arm Float Detent



3-Speed*



Hydraglide™ Ride Control*



High-Flow Auxiliary Hydraulics*

650 & 750 ARTICULATED LOADERS

PEC	IFICATIONS	650	750
DIMENSIONS	Height to Top of Cab / ROPS (mm)	8' 0" (2445)	8' 1" (2454)
	Width over Tires (mm)	5' 4" (1637)	6' 10" (2080)
	Length with Bucket on Ground (mm)	16' 11" (5155)	17' 8" (5382)
	Shipping Length - No Bucket (mm)	13' 9" (4200)	14' 4" (4376)
	Bucket Hinge Pin Height (mm)	10' 10" (3300)	11' 4" (3455)
	Maximum Dump Angle at Full Height	45°	45°
	Outer Turning Radius (mm)	10' 10" (3289)	11' 5" (3480)
	Articulation Angle from Center	45°	45°
CAPACITIES	Static Tipping Load with Bucket (kg)	6,173 lbs. (2800)	7,275 lbs. (3300)
	Bucket Breakout (kg)	9,791 lbs. (4441)	11,228 lbs. (5093)
	Operating Weight without Bucket (kg)	8,680 lbs. (3937)	9,935 lbs. (4506)
ENGINE	Engine Manufacturer	Yanmar	Deutz
	Model / Number of Cylinders	4TNV98T / 4	TD 3.6 L / 4
	Gross Power @ 2300 rpm (kW)	65 hp (49)	74 hp (55)
	Displacement (L)	202 cu in. (3.3)	220 cu in. (3.6)
HYDRAULICS	Work Hydraulic System Flow (L/min)	18.4 gpm (70)	18.4 gpm (70)
	Drive Hydraulic System Pressure (bar)	6,100 psi (420)	5,500 psi (380)
	Drive Hydraulic Reservoir Capacity (L)	19.5 gal. (73.7)	19.5 gal. (73.7)
ОТНЕК	Travel Speeds (km/hr)	7/12 mph (11/20)	5/12 mph (8/20)
	Battery	12 V	12 V
	Fuel Tank Capacity (L)	25 gal. (95)	27 gal. (102)
	Tires	405 / 70 20	550 / 45 R 22.5

SPECIFICATIONS ARE PRELIMINARY

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.





One Gehl Way, West Bend, WI 53095

GEHL COMPACT EQUIPMENT

Phone: (262) 334-9461

STANDARD FEATURES

- 4-Post Canopy ROPS and FOPS Certified
- Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- Hydrostatic 2-Speed Transmission
- Tilt and Lift Arm Float Detent
- Inching Pedal
- Digital Display with Audible and Visual Indicators
- Steering Column with Tilt and Extension Adjustments
- Differential Lock (Hydraulically Activated Front and Rear)
- Oscillating Front Frame
- Rubber Floormat
- Power-A-Tach® Attachment Mounting System (EuroStyle, 4-Point & Skid Steer)
- Adjustable Arm Rest
- Five-Way Adjustable Seat
- 12-Volt Socket in Arm Rest
- Tapered Z-Bar Loader Linkage with Mechanical Self-Level and Return-to-Dig
- Multi-Function Joystick
- Lift / Tilt Electronic Lockout Switch
- Reverse and Brake Tail Lights
- Emergency Lift Arm Lower Switch
- Master Electrical Disconnect Switch
- Articulation Locking Bar (conforms to SAEJ276)

OPTIONAL FEATURES

- 4-Post Canopy with Front and Rear Windows
- Cabin with Heat
- Cabin with Heat and Air Conditioning
- 3-Speed **650** 7 / 12 / 19 mph (11 / 20 / 30 km/hr) **750** 5 / 12 / 19 mph (8 / 20 / 30 km/hr)
- Five-Way Adjustable Air Suspension Seat
- LED Work Lights
- Speed Control
- Back-up Alarm
- Hydraglide™ Ride Control
- Rear Auxiliary Hydraulics
- Additional Set of Front Auxiliary Hydraulics
- High-Flow Auxiliary Hydraulics
- Radio
- Rotating Beacon
- Strobe Light
- Lockable Tool Box
- Engine Block Heater
- Side View Mirrors
- Front and Rear 12-Volt Electric Auxiliary
- License Plate Holder
- Electric Attachment Control 14-Pin Harness with Switches
- Rear Hitch Clevis
- Rear Hitch Receiver
- 3 inch (75 mm) Seatbelt